

ROTARY PISTON BURIAL VAULT VIBRATOR

- BETTER FINISH • FASTER POUR • STRONGER CONCRETE

STEEL FORMS – PIN BRACKETS (60-75% VIBRATION TRANSFER)

- Silent, meets OSHA regulations
- No lubrication needed
- Outlasts standard pistons 3 to 1
- Easily repaired; Not a throw away like standard piston vibrators



PNEUMATIC MODEL VSP-510

FORCE: 1000 lbs.
AIR. CONS: 21CFM
at 80 PSI
WEIGHT: 15 lbs.
DIM: 7"L x 4"W x 8"H
FREQUENCY: 4500 RPM



UPF-Female Bracket Welded To Form

Model VSP-510 Pneumatic Silent Turbine design and USP-900 Electric 115 Volt Pin Bracket Vibrators give the concrete precast producer a silent vibrator that needs no lubrication and a 115 volt plug in electric vibrator. These units are primarily used by the burial vault producer. Their noiseless operation makes them ideal for operating anyplace or anytime without disturbance. Their high frequency and rotary force create up to 1000 lbs. of force, removing air in the mixture faster, making the concrete stronger, with a blemish-free glass-like surface finish, eliminating pumping action and poor surface finish obtained by standard reciprocating piston vibrators. Both units are field repairable and not throw-aways like piston vibrators.

ELECTRIC MODEL USP-900

115 VOLT 4 AMPS
FORCE: 900 LBS.
WEIGHT: 18 LBS.
FREQUENCY: 9000 RPM

